



The AirPouch Express 3 Tabletop Void-fill System provides on-demand, easy-to-use air pillows for high packing productivity, reduced shipping costs, and increased customer satisfaction. Operating at speeds over 50 feet per minute in semi-or fully-automatic modes, the AirPouch Express 3 creates continuous strips of air pillows that are ideal for all protective packing applications. Weighing in at just 35 pounds, this compact, all-electric system features operator-friendly controls and virtually maintenance-free operation. Simply plug the unit in, load the air pillow material, and start packing.

3525D

B*

SMAI

The AirPouch Express 3 also offers a wide variety of accessories and integrated system configurations for optimum productivity in each unique application. Basic accessories can be added to the Express 3 to create a

simple, stand-alone packing station, or the system can be integrated into existing workstations for highproductivity, multi-user order fulfillment operations.

New! The Express 3 is the **first pre-formed pillow system to offer knifeless operation**, eliminating the primary wear item found on every other machine in its class. Instead, AirPouch air pillows use a patent-pending perforation that automatically separates for filling, then re-seals as it passes through the machine – without compromising speed or seal integrity. AirPouch pillows also feature our exclusive EZ-Tear[™] Perforations that are preferred for their easy handling and effortless pillow separation. AirPouch void-fill material feeds from a high-yield box, reducing changeovers and operator lifting. Material storage space is minimal.



AirPouch void-fill air pillows are available in a variety of material types, including standard EarthAware[™] Biodegradable and Recycled Films. These pillows offer superior seals and puncture resistance for durability and

AirPouch

reliable air retention. Air pillows offer the convenience and cleanliness not found in other void-fill products, such as EPS peanuts or paper. Protected products are easily identified inside the shipping carton, reducing waste and increasing customer satisfaction.

System-matched for optimum performance on the Express 3 system, AirPouch void-fill air pillows are available in a range of lengths, widths and mil gauges to suit any void-fill application requirement.

User Benefits

- Provides easy-to-use air pillows on-demand for fast, easy packing in semi- or fully-automatic modes
- Compact, tabletop system produces air pillow bags at speeds over 50 feet per minute
- Knifeless design eliminates the primary wear item found on other void-fill air pillow machines
- EZ-Tear Perforations are packer-friendly and designed for improved efficiency and ergonomics
- All-electric, portable system is lightweight and does not require compressed air
- Easy to install and simple to operate
- Boxed material requires less lifting and fewer changeovers
- Better air retention and improved yield reduce cost per cubic foc
- Dust-free air pillows reduce product loss and are cleaner to use than EPS peanuts
- · Lower shipping costs with lightweight pillows compared to paper



Standard Features

- All-electric design does not require compressed air to operate
- Compact and lightweight for portability
- Operator-friendly controls for easy set-up and operation
- Knifeless design eliminates primary wear item
- Adjustable air volume and run timer
- Reliable equipment requires minimal maintenance

<u>Options</u>

- Machine Stand
- Storage Hoppers
- Automatic Product Level Sensors
- Dispenser Attachments
- Footswitch
- Air Tower Overhead Hopper System
- Custom engineered solutions for unique packing station requirements

Typical Applications

- All void-fill applications, including:
- Mail order fulfillment
- Pharmaceutical fulfillment
- Third party logistics
- Contract packaging/fulfillment
- Electrical & electronic products
- Automotive & appliance parts
- Cosmetics, health & beauty aids
- Hobby & craft items
- Jewelry & novelty items



Express 3[™] uses EarthAware[™] Biodegradable and Recycled Films



Technical Specifications

35 lbs. (16 kg)	
L 20.5 x W 8.5 x H 14 in. (52 x 22 x 36	δ cm)
115/230 VAC; 50/60 Hz; 1.5/.75 FLA	
8" and 10" wide in various standard ler	ngths
1.5 mil Standard	2.0 mil
4000 ft./box	3000 ft./box
EarthAware [™] Biodegradable LLDPE or Recycled Film	EarthAware [™] Biodegradable LLDPE or Recycled Film
Stock printed with EarthAware logo for awareness; Green tint	Stock printed with EarthAware logo for awareness; Green tint
	L 20.5 x W 8.5 x H 14 in. (52 x 22 x 36 115/230 VAC; 50/60 Hz; 1.5/.75 FLA 8" and 10" wide in various standard ler 1.5 mil Standard 4000 ft./box EarthAware [™] Biodegradable LLDPE or Recycled Film Stock printed with EarthAware logo

AirPouch

Other Film

Types Available: DuraClear™ LLDPE (clear), Biodegradable LLDPE (clear), and APStat™ Anti-Static





Mechanical Features

Compact, all-electric design and operatorfriendly controls for easy set-up and operation



Optional accessories enable an integrated system that is unique to each packing application



Produces continuous strips of air pillows with EZ-Tear[™] Perforations for easy handling and effortless pillow separation



Automated Packaging Systems Inc. 10175 Philipp Parkway Streetsboro, Ohio 44241 Tel: 888-288-6224 Fax: 330-342-2400

Visit or call us at www.airpouch.com 888-288-6224

© 2009 Automated Packaging Systems APS 06/09 10M Features, Options and Technical Specifications subject to change